

9000 SERIES DRILL



SIMPLY THE PERFECT PACKAGE FOR SUPERIOR SEEDING THE NEW 9000 SERIES DRILL

The new Connor Shea 9000 Series Drill packages recent advancements with the core features and elegant simplicity of the classic CSN 8000 Series machines.

Coil tynes give predictable performance and take the hard work out of maintenance. The included coulter bar and trailing hitch kit make short work of tough conditions.

No power? No problem! The 9000 Series comes as standard with our time-proven, infinitely variable speed, oil bath gearbox. Of course, electric drive is also an option.

Sowing widths from 2.03m (6' 7") to 3.34m (10'11") are available with seeding

spacings of either 127mm (5") or 152mm (6"). Ideal for boosting pasture density on small to medium size holdings.

















FEATURES

INFINITELY VARIABLE GEARBOX

The 9000 Series Drill is equipped with an infinitely variable speed, oil bath gearbox. Select any rate between 1 kg/ha and 240 kg/ha.

The low-maintenance traction drive makes this model ideal for tractors where electric drive would be inconvenient or impractical. Electric Drive is available as an option where appropriate.

STANDARD COULTER BAR

The included front coulter bar helps break up compacted soils or heavy trash, easing the way for the openers. Coulters are available in either 13-3/8" plain or 16" fluted.

STANDARD TRAILING HITCH KIT

In tandem with the front coulter bar, the trailing hitch kit is included as standard equipment.

EASE OF OPERATION

Gas struts on the hopper lid, remote greasing for the seed and fertilizer shaft bearings and a large platform with handrail keep things easy.

HYDRAULIC DEPTH CONTROL ②

Precisely control the sowing depth of the machine and easily raise the tynes for transport, all at the pull of a lever.

EVER-RELIABLE COIL TYNES 3

For simple and robust you can't go past Connor Shea Coil Tynes. With nothing to grease or go out of adjustment, coil tynes are the pinnacle of predictable performance.



SPECIFICATIONS

MECHANICAL GEARBOX DRIVE	ELECTRIC DRIVE (OPTIONAL)	TRANSPORT WIDTH	SOWING WIDTH	SOWING ROWS	ROW SPACING	MAX. HEIGHT	WEIGHT EMPTY	WEIGHT FULL	SEED CAPACITY	FERT. CAPACITY	TYRES
900020M152CT	900020E152CT	2.06m	1.98m	13	152mm (6")	2.425m	1259kg	1792kg	239.43L	288.82L	235/75x15"
900024M152CT	900024E152CT	2.51m	2.43m	16	152mm (6")	2.425m	1348kg	1987kg	287.43L	346.72L	235/75x15"
900028M152CT	900028E152CT	2.95m	2.89m	19	152mm (6")	2.425m	1437kg	2182kg	335.44L	404.63L	215/85x16"
900033M152CT	900033E152CT	3.42m	3.34m	22	152mm (6")	2.425m	1577kg	2456kg	395.45L	477.02L	215/85x16"
900020M127CT	900020E127CT	2.06m	2.03m	16	127mm (5")	2.425m	1305kg	1837kg	239.43L	288.82L	235/75x15"
900024M127CT	900024E127CT	2.51m	2.41m	19	127mm (5")	2.425m	1394kg	2033kg	287.43L	346.72L	235/75x15"
900028M127CT	900028E127CT	2.95m	2.79m	22	127mm (5")	2.425m	1482kg	2228kg	335.44L	404.63L	215/85x16"
900033M127CT	900033E127CT	3.42m	3.30m	26	127mm (5")	2.425m	1638kg	2517kg	395.45L	477.02L	215/85x16"

Due to our policy of continuing research, specifications are subject to change without prior notice.



CONNOR SHEA — a John Shearer Company

PHONE: 08 8468 4190

EMAIL: sales@johnshearer.com.au WEB: johnshearer.com.au

John Shearer Pty. Ltd.

POST: HQ: PO Box 2466 Regency Park, SA 5942 34 Burleigh Avenue, Woodville North, SA 5012