



# JOHN SHEARER FOLDING WING TRASHWORKER



## AUSTRALIA'S TIME-PROVEN TRASHWORKER PLATFORM

The Shearer Folding Wing Trashworker is designed for low maintenance with minimal moving parts. The machine is designed for primary and secondary tillage in trash farming, stubble mulch cultivation and chisel ploughing to break up hard pans. It is also able to be adapted for trashseeding.

### ROBUST AND ADAPTABLE

Greasable hardened pins and bushes are fitted on all critical, high load pivots.

Excellent trash clearance, wide lead between rows and a proven tyne layout make this machine an impeccable trashworker.

A narrow, 254mm (10") tyne spacing option is available for summer crop sowing.

All models now come with an upgraded 10L gas accumulator as standard.

In combination with an airseeder, these models can also be employed in trashseeding.

- ✓ **PROVEN ROBUST CONSTRUCTION**  
For a long service life in harsh conditions.
- ✓ **1000LBS EDGE-ON-TYNES**  
A big step up from the 650lbs flat-on-tyne.
- ✓ **LEVEL LIFT CYLINDERS**  
For equal working depth.
- ✓ **EXCELLENT TRASH CLEARANCE**  
Wide lead between rows and proven tyne layout.
- ✓ **LOW MAINTENANCE**  
Few moving parts with greasable hardened pins and bushes on all critical, high load pivots.



Scan the QR code to see  
this machine online

 **AUSTRALIAN  
OWNED AND MADE**

## MODELS

Model	Tynes	Width	Layout	Row Spacing
3721304	19	5.8m (19')	Rigid	305mm (12")
3722302	23	7.0m (23')	Single Fold	305mm (12")
3722902	29	8.8m (29')	Single Fold	305mm (12")
3723502	35	10.7m (35')	Single Fold	305mm (12")
3724105	41	12.5m (41')	Single Fold	305mm (12")
	27	7.0m (23')	Single Fold	254mm (10")
	35	8.8m (29')	Single Fold	254mm (10")
	41	10.7m (35')	Single Fold	254mm (10")

## OPTIONS AND ACCESSORIES

Model	Description
37250-5002	2 tyne extension Not available for 41 tyne machines

10 litre Gas Accumulator in lieu of 4 litre now standard on all sizes

## HYDRAULIC TYNES

The John Shearer 1000lb Hydraulic Tyne Assembly is tough and reliable and offers on the go tyne breakout pressure adjustment from the tractor seat.

Breakout pressure is adjustable from 0.4kN (100lb) up to 4.4kN (1000lb). The easy to fit clamp on design mounts onto 100mm x 100mm (4" x 4") heavy duty RHS beams.

The full, unimpeded jump height is available at all pressure settings.

Additionally, the streamlined 50mm x 32mm (2" x 1¼") Edge-on Tyne improves trashflow and reduces draft.

Transport width may be reduced to 4.7m (15'5") by reducing hydraulic pressure on tynes and 'pushing back'.



Need a smaller machine? See our 7/9/11 tyne **Linkage Trashworker** and 13/15/17 tyne **Stubby Trashworker** models on the website.

## SPECIFICATIONS

	23 Tyne	29 Tyne	35 Tyne	41 Tyne
Width of cut	7m (23')	8.8m (29')	10.7m (35')	12.5m (41')
Power (Sweeps)	85 - 105 Kw (115 - 145 HP)	110 - 130 Kw (150 - 175HP)	130 - 155 Kw (175 - 210 HP)	155 - 180Kw (210 - 240HP)
Power (Deep chiselling)	up to 225 Kw (305 HP)	up to 280 Kw (375 HP)	up to 340 Kw (460 HP)	up to 400 Kw (540 HP)
Approx. weight	4,340kg (9,548lb)	4,870kg (10,714lb)	5,475kg (12,045lb)	5,850kg (12,870lb)
Packed Length	4.3m (14')	4.3m (14')	4.3m (14')	4.9m (16')
Packed Width	2.9m (9'6")	2.9m (9'6")	2.9m (9'6")	2.9m (9'6")
Packed Height	1.63m (5'4")	2.44m (8')	2.13m (7')	2.13m (7')

Tyne Transport Clearance	200mm (8")
Transport Width	5.5m (17'10")
Maximum working depth	360mm
Under-frame Clearance	770mm
Wheel Equipment	<b>Centre and Wings:</b> 12.5/80-18 x 16 ply

Tyne Ranks	4
Spacing Between Ranks	1 & 2: 770mm 2 & 3 and 3 & 4: 950mm
Tyne Spacing	305mm (12") or 254mm (10")
Tyne breakout	Up to 454kg (1,000lb)

Due to our policy of continuing research, specifications are subject to change without prior notice.

**Shearer**  
EST. 1877

PHONE: 08 8468 4190  
EMAIL: sales@johnshearer.com.au  
WEB: johnshearer.com.au

John Shearer Pty. Ltd.  
PO Box 2466 Regency Park, SA 5942  
HQ: 34 Burleigh Avenue, Woodville North, SA 5012